

F1270



MANUGRAPH
Technology in Print

F1270

Maximum Printing Speed	70,000 cph.
Web width	Minimum 510 mm (20 inches) Maximum 915 mm (36inches)
Cut-off Length	546, 560, 578 mm (21 ¹ / ₂ , 22, 22 ³ / ₄ inches)
Jaw cylinder ratio	2 - around cutting cylinder 3 - around pln/tucking cylinder 4 - around jaw cylinder
Type of folds	Half fold (Broadsheet) Quarter fold

- Cylinder Ratio 2:3:4
- Robust heavy duty construction
- Straight & Collect folding options
- 12 web capacity over lower former
- Optional - 2 Hi or 3 Hi former arrangement, 4th former as a side former
- Shafted or Shaftless drive
- Suitable for single wide (2x1 & 2x2) and double wide (4x1 & 4x2) presses
- On the run adjustments for Lap, Pin release & Bucket wheel timings
- Automatic central greasing system (Optional)
- 3 sets of nip rollers with pneumatic controls
- Shaftless Quarter fold with pecking style chopper
- Push button change-over for 2nd fold to Quarter fold & Straight to Collect mode
- Optional - Cross perforation with on-the-run phasing, Skip slitter & inline Stitcher



Manugraph India Ltd.

Sidhwa House, N.A. Sawant Marg, Colaba, Mumbai - 400 005, India. Phone: 91-22-2287 4815/4788/1191/0620.

Fax: +91 22 2287 0702 Email: sales@manugraph.com Website: www.manugraph.com

F1270 is subject to continuous upgradation resulting from ongoing research and development and practical experiences gained. Therefore, in the interest of the customers we reserve the right to modify the specifications, features and technical data without notice. Only the specifications while confirming the order shall be binding.